

# UNIRACK

## Universal amplification solution

UNIRACK is part of the universal solution of APG amplification intended for the world of entertainment, touring and performance halls wishing to comply with Live operating standards.

UNIRACK can be used for all live sound applications in the APG range, from the smallest speakers to complete sound reinforcement systems.

UNIRACK consists of the following components:

- 4u flight case - 60 x 60 x 29 cm with sliding doors
- PC16A Mono Power Cable
- Front-panel connection ports (I/O + network)

UNIRACK is directly compatible with TOURACK and allows it to expand the total number of inputs/outputs from 8x8 to 12x12 and to be powered directly via the AUX 1 jack on the TOURACK's power distribution panel.

All audio wiring is routed through the front panel for greater clarity and easier interaction with the touchscreens on the DA Series amplifiers.

All connectors comply with Neutrik's "D Series Universal" standard to ensure the durability required for live and touring applications and interoperability with existing equipment.




Illustration - UNIRACK equipped with a DA12 amplifier

- APG usage standards for touring and "cross-renting".
- All sound reinforcement applications in the APG range.
- Rack with 4 inputs / 4 outputs processed and amplified.
- Analog and digital inputs (AES3 or Dante).
- Connections for analog and AES3 inputs.
- 2 Ethernet ports for remote control.
- Speakon™ NL4 and NL8 outputs.
- Cabling on the front of the rack.
- Compatibility with TOURACK.


**APG**

# UNIRACK


## Technical Specifications




Front (closed)



Side



Front (open)



Rear (open)

### Specifications :

#### Inputs

Analog	4 female XLR connectors 4 male XLR connectors (LINK)
AES3 Digital Outputs	2 Female XLR (4-channel audio) 2 Male XLR (LINK)
Digital DANTE / AES67	2 Ethercon™ (4 audio channels)

#### Outputs

4 Speakon™ NL4	(4 speaker channels)
1 Speakon™ NL8	(4 speaker channels)
4 Dante/AES67 TX	(via Ethernet connectors)

#### Power supply

Power connector	IEC C20 power connector (20A max) - included with the amplifier
-----------------	---

#### Components

UNIRACK	4U Flight Case
RP1UMI-DA1	DA Input patch for Unirack and Tourack amplifier 1 <sup>(1)</sup>
RP1UMO4	Output patch for Unirack and Tourack amplifier 1 <sup>(1)</sup>

#### Construction and physical characteristics

Dimensions (H, W, D) (mm)	290 x 600 x 600
Weight (kg)	36 kg (equipped with <sup>1</sup> DA12 amplifier)
Handles	4 Flight Case Handles
Doors	Sliding Doors
Suspension	Silent Blocks
Stainless Steel Top Panel for specific information from the live service provider	

(1) Amplifier sold separately. The connection plates and flight case cannot be sold separately and are sold as a single "UNIRACK" item.

Rack designed to hold only one DA Series amplifier (DA8 / DA12) inside, excluding any other amplifier models.

(2) Ethernet switch and router not included.

**5 YEARS WARRANTY** A five-year comprehensive warranty covers filters and transducers against any manufacturing defects under normal product use.

Release Date: March 2026 / DOP\_1831\_B

APG maintains a policy of continuous research and development aimed at improving its products. For this reason, new materials, manufacturing methods, and design changes may be introduced without prior notice. As a result, an APG product may differ in certain respects from its published description; however, unless otherwise specified, its specifications will be equal to or exceed those published.

**APG**

ARBANE GROUP - 8 Rue Johannes Gutenberg, 44340 BOUGUENAI - FRANCE  
Tel.: +33 (0)2 40 46 66 64 - Email: contact@apg.audio - www.apg.audio

**arbane**  
groupe